

Illinois

Implementation
Guide
For
Electronic
Data
Interchange

Transaction Set
ANSI ASC X12 Version 004010

814

Historical Usage Request

Version x.x

Summary of Changes

Month ##, 2008

- Initial Release.

Implementation Notes

Transaction Reference Numbers	<ul style="list-style-type: none"> On the Request, the Transaction Reference Number in the BGN02 must be unique over time. This number will be returned in the BGN06 of the Response transaction.
LIN01 Reference Numbers	<ul style="list-style-type: none"> On the Request, the identifier in the LIN01 element either by itself, or in conjunction with the BGN02 element from the BGN segment, must uniquely identify each LIN request item over time. This number will be returned on the Response transaction in the same element.
Definition of Mass Market Customers	<ul style="list-style-type: none"> Ameren Mass Market - Includes any account containing one or more of only the following types of service point: DS-1 (residential), DS-2 (small commercial < 150 kW) or DS-5 (lighting). ComEd Mass Market – Includes all residential and commercial customers under 100 kW.
Definition of Service Point	<ul style="list-style-type: none"> Ameren’s systems operate at a Service Point level. A service point consists of metered or unmetered load that is assigned to a specific Ameren rate. A service point containing metered load can have one or more meters associated with it. An Ameren account may have multiple electric service points associated with it. For Mass Market accounts, the RES is required to take all service points on the account that is being enrolled. For Non-Mass Market accounts, the RES may choose which Service Points to serve. It is important to follow the requirements in each Implementation Guide to differentiate when a Service Point Identifier may or may not be sent. ComEd operates at an Account Level only.
814 HU Requests at Account Level Only	<ul style="list-style-type: none"> The Service Point Identifier (REF*LU) was not included in the Request transaction because Ameren only allows Historical Usage to be requested at an account level. If it was provided on the Request transaction, it will be ignored. Service Point Numbers will be included in the Response transaction for Ameren Non-Mass Market accounts. All 867 Historical Usage transactions will be sent at the Service Point Level. If multiple Service Points exist, one 867 will be sent for each Service Point.
HU vs. HI	<ul style="list-style-type: none"> If a RES requests Historical Usage (LIN05 = “HU”), the utility will send the 867 Historical Usage transaction. If a RES requests Historical Interval Usage (LIN05 = “HI”), they will receive the interval details as described below. If a RES requests Historical Interval Usage (LIN05 = “HI”), and the account does not contain Interval meters, the utility will send the 867 Historical Usage transaction.
Historical Interval Usage	<ul style="list-style-type: none"> Ameren allows for Historical Interval Usage to be requested via EDI and the data will be returned via an EDI 867 Historical Usage transaction including PTD Loops SU, BQ and FG. ComEd allows for Historical Interval Usage to be requested via EDI and the 814 HU Response will contain a link where the information may be downloaded. Any applicable charges are applied to the RES non-service account.

814 General Request, Response or Confirmation

Functional Group ID=**GE**

Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the General Request, Response or Confirmation Transaction Set (814) for use within the context of an Electronic Data Interchange (EDI) environment. This standard can be used to request actions to be performed, to respond to a request for actions to be performed or to confirm information related to actions performed.

Heading:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
M	010	ST	Transaction Set Header	M	1		
M	020	BGN	Beginning Segment	M	1		
			LOOP ID - N1			>1	
	040	N1	Name	O	1		n1

Detail:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
			LOOP ID - LIN			>1	
	010	LIN	Item Identification	O	1		
	020	ASI	Action or Status Indicator	O	1		
	030	REF	Reference Identification	O	>1		
M	150	SE	Transaction Set Trailer	M	1		

Transaction Set Notes

1. The N1 loop is used to identify the transaction sender and receiver.

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Semantic Notes: 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
Comments:
Notes: Required
 ST~814~000000001

Data Element Summary

	Ref.	Data	Attributes
	Des.	Element Name	
Must Use	ST01	143 Transaction Set Identifier Code	M ID 3/3
		Code uniquely identifying a Transaction Set	
		814 General Request, Response or Confirmation	
Must Use	ST02	329 Transaction Set Control Number	M AN 4/9
		Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	

Segment: **BGN** Beginning Segment
Position: 020
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the beginning of a transaction set
Syntax Notes: 1 If BGN05 is present, then BGN04 is required.
Semantic Notes: 1 BGN02 is the transaction set reference number.
 2 BGN03 is the transaction set date.
 3 BGN04 is the transaction set time.
 4 BGN05 is the transaction set time qualifier.
 5 BGN06 is the transaction set reference number of a previously sent transaction affected by the current transaction.

Comments:

Notes:

Required
 BGN~13~20091215123000001~20091215

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	BGN01	353	Transaction Set Purpose Code Code identifying purpose of transaction set 13 Request	M ID 2/2
Must Use	BGN02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier A unique transaction identification number assigned by the originator of this transaction. This number must be unique over time. Transaction Reference Numbers will only contain uppercase letters (A to Z), digits (0 to 9), dashes (-) and periods (.). Note that all other characters (spaces, underscores, etc.) must be excluded.	M AN 1/30
Must Use	BGN03	373	Date Date expressed as CCYYMMDD The transaction creation date - the date that the data was processed by the sender's application system.	M DT 8/8

Segment: **N1** Name (Utility)
Position: 040
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: 1
Purpose: To identify a party by type of organization, name, and code
Syntax Notes: 1 At least one of N102 or N103 is required.
 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:
Comments: 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
 2 N105 and N106 further define the type of entity in N101.
Notes: Required
 N1~8S~UTILITY NAME~1~007909411

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u> <u>Name</u>	
Must Use	N101	98 Entity Identifier Code	M ID 2/3
		Code identifying an organizational entity, a physical location, property or an individual	
		8S Consumer Service Provider (CSP)	
		Utility	
Must Use	N102	93 Name	X AN 1/60
		Free-form name	
		Utility Name	
Must Use	N103	66 Identification Code Qualifier	X ID 1/2
		Code designating the system/method of code structure used for Identification Code (67)	
		1 D-U-N-S Number, Dun & Bradstreet	
		9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix	
Must Use	N104	67 Identification Code	X AN 2/80
		Code identifying a party or other code	
		Utility D-U-N-S or D-U-N-S+4 Number	

Segment: **N1** Name (Retail Electric Supplier)
Position: 040
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: 1
Purpose: To identify a party by type of organization, name, and code
Syntax Notes: 1 At least one of N102 or N103 is required.
 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:
Comments: 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
 2 N105 and N106 further define the type of entity in N101.
Notes: Required
 N1~SJ~RES COMPANY~1~049612345

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u> <u>Name</u>	
Must Use	N101	98 Entity Identifier Code	M ID 2/3
		Code identifying an organizational entity, a physical location, property or an individual	
		SJ Service Provider	
		Retail Electric Supplier (RES)	
Must Use	N102	93 Name	X AN 1/60
		Free-form name	
		RES Name	
Must Use	N103	66 Identification Code Qualifier	X ID 1/2
		Code designating the system/method of code structure used for Identification Code (67)	
		1 D-U-N-S Number, Dun & Bradstreet	
		9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix	
Must Use	N104	67 Identification Code	X AN 2/80
		Code identifying a party or other code	
		RES D-U-N-S or D-U-N-S+4 Number	

Segment: **N1** Name (Customer)
Position: 040
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: 1
Purpose: To identify a party by type of organization, name, and code
Syntax Notes: 1 At least one of N102 or N103 is required.
 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:
Comments: 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
 2 N105 and N106 further define the type of entity in N101.
Notes: Optional
 N1~8R~CUSTOMER NAME

Data Element Summary

	Ref. Des.	Data Element	Name	Attributes
Must Use	N101	98	Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual 8R Consumer Service Provider (CSP) Customer Customer Name	M ID 2/3
Must Use	N102	93	Name Free-form name Customer Name	X AN 1/60

Segment: **LIN** Item Identification
Position: 010
Loop: LIN Optional
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify basic item identification data
Syntax Notes:

- 1 If either LIN04 or LIN05 is present, then the other is required.
- 2 If either LIN06 or LIN07 is present, then the other is required.
- 3 If either LIN08 or LIN09 is present, then the other is required.
- 4 If either LIN10 or LIN11 is present, then the other is required.
- 5 If either LIN12 or LIN13 is present, then the other is required.
- 6 If either LIN14 or LIN15 is present, then the other is required.
- 7 If either LIN16 or LIN17 is present, then the other is required.
- 8 If either LIN18 or LIN19 is present, then the other is required.
- 9 If either LIN20 or LIN21 is present, then the other is required.
- 10 If either LIN22 or LIN23 is present, then the other is required.
- 11 If either LIN24 or LIN25 is present, then the other is required.
- 12 If either LIN26 or LIN27 is present, then the other is required.
- 13 If either LIN28 or LIN29 is present, then the other is required.
- 14 If either LIN30 or LIN31 is present, then the other is required.

Semantic Notes:

- 1 LIN01 is the line item identification

Comments:

- 1 See the Data Dictionary for a complete list of IDs.
- 2 LIN02 through LIN31 provide for fifteen different product/service IDs for each item.
For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Notes: Required - Only one LIN Loop will be sent.
LIN~1~SH~EL~SH~HU
LIN~1~SH~EL~SH~HI

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	LIN01	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set On the Request, identifier supplied in this element either by itself or in conjunction with the BGN02 element from the BGN segment must uniquely identify each LIN request item over time. This number will be returned on the Response transaction in the same element.	O AN 1/20
Must Use	LIN02	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) SH Service Requested	M ID 2/2
Must Use	LIN03	234	Product/Service ID Identifying number for a product or service EL Electric	M AN 1/48
Must Use	LIN04	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) SH Service Requested	X ID 2/2
Must Use	LIN05	234	Product/Service ID Identifying number for a product or service HI Historical Interval Usage Request to obtain Historical Interval Usage Ameren: If the intervals are available, Ameren will send the 867 Historical Interval Usage transaction. ComEd: If the intervals are available, ComEd will post	X AN 1/48

the file to a website and include the URL for that file on the 814 Accept Response.

If the intervals are not available (e.g., the account does not have interval meters), the Utility will send an 814 Accept Response with the Status Reason Code HIU and, if available, send the 867 Historical Usage transaction with the summarized data.

If Historical Usage was blocked by the customer, the Utility will send an 814 Accept Response with the Status Reason Code HUR.

HU

Historical Usage

Request to obtain Historical Usage

If Historical Usage is not available, the Utility will send an 814 Accept Response with the Status Reason Code HUU.

If Historical Usage was blocked by the customer, the Utility will send an 814 Accept Response with the Status Reason Code HUR.

Segment: **ASI** Action or Status Indicator
Position: 020
Loop: LIN Optional
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To indicate the action to be taken with the information provided or the status of the entity described

Syntax Notes:
Semantic Notes:
Comments:
Notes:

Required
ASI~7~029

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	ASI01	306	Action Code Code indicating type of action 7 Request	M ID 1/2
Must Use	ASI02	875	Maintenance Type Code Code identifying the specific type of item maintenance 029 Inquiry	M ID 3/3

Segment: **REF** Reference Identification (RES Account Number)
Position: 030
Loop: LIN Optional
Level: Detail
Usage: Optional
Max Use: >1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:
Notes:

Optional
REF~11~1234567890

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification 11 Account Number Retail Electric Supplier (RES) Account Number	M ID 2/3
Must Use	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier RES Account Number	X AN 1/30

Segment: **REF** Reference Identification (Utility Account Number)
Position: 030
Loop: LIN Optional
Level: Detail
Usage: Optional
Max Use: >1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:
Notes:

Required
 Both utilities currently have 10 digit account numbers. All 10 digits, including leading zeros must be provided.
 REF~12~0000445648

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification 12 Billing Account Utility Account Number	M ID 2/3
Must Use	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier Utility Account Number	X AN 1/30

Segment: **SE** Transaction Set Trailer
Position: 150
Loop:
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Syntax Notes:

Semantic Notes:

Comments: 1 SE is the last segment of each transaction set.

Notes: Required
SE~13~000000001

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	SE01	96	Number of Included Segments Total number of segments included in a transaction set including ST and SE segments	M N0 1/10
Must Use	SE02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9

Example #1 – Historical Usage Request

ST*814*0001
BGN*13*2010063000001*20100630
N1*8S*UTILITY*1*006912345
N1*SJ*SUPPLIER*9*007909111IL00
N1*8R*CUSTOMER NAME
LIN*1*SH*EL*SH*HU
 ASI*7*029
 REF*11*0012345600
 REF*12*0312345624
SE*10*0001

Gray segments are optional or dependent.

Example #2 – Historical Interval Usage Request

ST*814*0001
BGN*13*2010063000001*20100630
N1*8S*UTILITY*1*006912345
N1*SJ*SUPPLIER*9*007909111IL00
N1*8R*CUSTOMER NAME
LIN*1*SH*EL*SH*HI
 ASI*7*029
 REF*11*0012345600
 REF*12*0312345624
SE*10*0001