

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Semantic Notes: 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
Comments:
Notes: Required
 ST~814~000000001

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	ST01	143	Transaction Set Identifier Code Code uniquely identifying a Transaction Set 814 General Request, Response or Confirmation	M ID 3/3
Must Use	ST02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9

Segment: **BGN** Beginning Segment
Position: 020
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the beginning of a transaction set
Syntax Notes: 1 If BGN05 is present, then BGN04 is required.
Semantic Notes: 1 BGN02 is the transaction set reference number.
 2 BGN03 is the transaction set date.
 3 BGN04 is the transaction set time.
 4 BGN05 is the transaction set time qualifier.
 5 BGN06 is the transaction set reference number of a previously sent transaction affected by the current transaction.

Comments:

Notes:

Required
 BGN~13~20091215123000001~20091215

Data Element Summary

	Ref. Des.	Data Element	Name	Attributes
Must Use	BGN01	353	Transaction Set Purpose Code Code identifying purpose of transaction set 13 Request	M ID 2/2
Must Use	BGN02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier A unique transaction identification number assigned by the originator of this transaction. This number must be unique over time. Transaction Reference numbers will only contain uppercase letters (A to Z) and digits (0 to 9). Note that punctuation (spaces, dashes, etc.) must be excluded.	M AN 1/30
Must Use	BGN03	373	Date Date expressed as CCYYMMDD The transaction creation date - the date that the data was processed by the sender's application system.	M DT 8/8

Segment: **N1** Name (Utility)
Position: 040
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: 1
Purpose: To identify a party by type of organization, name, and code
Syntax Notes: 1 At least one of N102 or N103 is required.
2 If either N103 or N104 is present, then the other is required.
Semantic Notes:
Comments: 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2 N105 and N106 further define the type of entity in N101.
Notes: Required
N1~8S~UTILITY NAME~1~007909411

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	N101	98	Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual 8S Consumer Service Provider (CSP) Utility	M ID 2/3
Must Use	N102	93	Name Free-form name Utility Name	X AN 1/60
Must Use	N103	66	Identification Code Qualifier Code designating the system/method of code structure used for Identification Code (67) 1 D-U-N-S Number, Dun & Bradstreet 9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix	X ID 1/2
Must Use	N104	67	Identification Code Code identifying a party or other code Utility D-U-N-S or D-U-N-S+4 Number	X AN 2/80

Segment: **N1** Name (Retail Electric Supplier)
Position: 040
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: 1
Purpose: To identify a party by type of organization, name, and code
Syntax Notes: 1 At least one of N102 or N103 is required.
 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:
Comments: 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
 2 N105 and N106 further define the type of entity in N101.
Notes: Required
 N1~SJ~RES COMPANY~1~049612345

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	N101	98	Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual SJ Service Provider Retail Electric Supplier (RES)	M ID 2/3
Must Use	N102	93	Name Free-form name RES Name	X AN 1/60
Must Use	N103	66	Identification Code Qualifier Code designating the system/method of code structure used for Identification Code (67) 1 D-U-N-S Number, Dun & Bradstreet 9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix	X ID 1/2
Must Use	N104	67	Identification Code Code identifying a party or other code RES D-U-N-S or D-U-N-S+4 Number	X AN 2/80

Segment: **N1** Name (Customer)
Position: 040
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: 1
Purpose: To identify a party by type of organization, name, and code
Syntax Notes:

- 1 At least one of N102 or N103 is required.
- 2 If either N103 or N104 is present, then the other is required.

Semantic Notes:
Comments:

- 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
- 2 N105 and N106 further define the type of entity in N101.

Notes: Required
N1~8R~CUSTOMER NAME

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	N101	98	Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual 8R Consumer Service Provider (CSP) Customer Customer Name	M ID 2/3
Must Use	N102	93	Name Free-form name Customer Name	X AN 1/60

Segment: **PER** Administrative Communications Contact

Position: 080

Loop: N1 Optional

Level: Heading

Usage: Optional

Max Use: >1

Purpose: To identify a person or office to whom administrative communications should be directed

Syntax Notes: 1 If either PER03 or PER04 is present, then the other is required.

2 If either PER05 or PER06 is present, then the other is required.

3 If either PER07 or PER08 is present, then the other is required.

Semantic Notes:

Comments:

Notes:

RES to Utility: Not Used
Utility to RES: Optional
PER~IC~CUSTOMER NAME~TE~6305551212

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
Must Use	PER01	366	Contact Function Code Code identifying the major duty or responsibility of the person or group named IC Information Contact	M ID 2/2
	PER02	93	Name Free-form name Customer Name	O AN 1/60
Must Use	PER03	365	Communication Number Qualifier Code identifying the type of communication number TE Telephone	X ID 2/2
Must Use	PER04	364	Communication Number Complete communications number including country or area code when applicable Customer Telephone Number	X AN 1/80

Segment: **LIN** Item Identification

Position: 010

Loop: LIN Optional

Level: Detail

Usage: Optional

Max Use: 1

Purpose: To specify basic item identification data

Syntax Notes:

- 1 If either LIN04 or LIN05 is present, then the other is required.
- 2 If either LIN06 or LIN07 is present, then the other is required.
- 3 If either LIN08 or LIN09 is present, then the other is required.
- 4 If either LIN10 or LIN11 is present, then the other is required.
- 5 If either LIN12 or LIN13 is present, then the other is required.
- 6 If either LIN14 or LIN15 is present, then the other is required.
- 7 If either LIN16 or LIN17 is present, then the other is required.
- 8 If either LIN18 or LIN19 is present, then the other is required.
- 9 If either LIN20 or LIN21 is present, then the other is required.
- 10 If either LIN22 or LIN23 is present, then the other is required.
- 11 If either LIN24 or LIN25 is present, then the other is required.
- 12 If either LIN26 or LIN27 is present, then the other is required.
- 13 If either LIN28 or LIN29 is present, then the other is required.
- 14 If either LIN30 or LIN31 is present, then the other is required.

Semantic Notes:

- 1 LIN01 is the line item identification

Comments:

- 1 See the Data Dictionary for a complete list of IDs.
- 2 LIN02 through LIN31 provide for fifteen different product/service IDs for each item.
For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Notes: Required

Ameren: One LIN Loop may be sent for each Service Point on an Account. Please see Ameren documentation for which accounts may be dropped at the Service Point level. Mass Market accounts may only be dropped at an account level.

ComEd: Only One LIN Loop may be sent per 814 transaction
LIN~1~SH~EL~SH~CE

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	LIN01	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set On the Request, identifier supplied in this element either by itself or in conjunction with the BGN02 element from the BGN segment must uniquely identify each LIN request item over time. This number will be returned on the Response transaction in the same element. If dropping by account for Ameren, and the account has multiple service points, each service point LIN on the Response will contain the single identifier provided in the request.	O AN 1/20
Must Use	LIN02	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) SH Service Requested	M ID 2/2
Must Use	LIN03	234	Product/Service ID Identifying number for a product or service EL Electric	M AN 1/48
Must Use	LIN04	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X ID 2/2

			SH	Service Requested		
Must Use	LIN05	234	Product/Service ID		X	AN 1/48
				Identifying number for a product or service		
			CE	Energy Services		
	LIN06	235	Product/Service ID Qualifier		X	ID 2/2
				Code identifying the type/source of the descriptive number used in Product/Service ID (234)		
				Ameren: Optional		
				ComEd: Not Used		
			SH	Service Requested		
	LIN07	234	Product/Service ID		X	AN 1/48
				Identifying number for a product or service		
				Ameren: Optional		
				ComEd: Not Used		
			SW	Off Cycle Drop		
				Request for a special meter read for a customer to drop off cycle, i.e., not at the next, regularly scheduled meter read. DTM~MRR is required when requesting an off-cycle read.		

Segment: **ASI** Action or Status Indicator
Position: 020
Loop: LIN Optional
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To indicate the action to be taken with the information provided or the status of the entity described

Syntax Notes:
Semantic Notes:
Comments:
Notes:

Required
 ASI~F~024

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	ASI01	306	Action Code Code indicating type of action A4 Pended F Final	M ID 1/2
			Used to notify a RES that a customer has indicated that they will be finalling their account. A transaction with this code is for information purposes only. The RES remains the active RES of record until an 814 Drop with an "F" (Final) indicator is received.	
Must Use	ASI02	875	Maintenance Type Code Code identifying the specific type of item maintenance 024 Cancellation or Termination	M ID 3/3

Segment: **REF** Reference Identification (RES Account Number)
Position: 030
Loop: LIN Optional
Level: Detail
Usage: Optional
Max Use: >1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:
Notes:

RES to Utility - Optional
 Utility to RES - Required if provided on the 814 Enrollment or 814 Change transactions.
 REF~11~1234567890

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Identification Qualifier	M ID 2/3
			Code qualifying the Reference Identification	
			11 Account Number	
			Retail Electric Supplier (RES) Account Number	
Must Use	REF02	127	Reference Identification	X AN 1/30
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	
			RES Account Number	

Segment: **REF** Reference Identification (Utility Account Number)
Position: 030
Loop: LIN Optional
Level: Detail
Usage: Optional
Max Use: >1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:
Notes:

Required

Both utilities currently have 10 digit account numbers. All 10 digits, including leading zeros must be provided.
 REF~12~0000445648

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification 12 Billing Account Utility Account Number	M ID 2/3
Must Use	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier Utility Account Number	X AN 1/30

Segment: **REF** Reference Identification (Service Point Identifier)
Position: 030
Loop: LIN Optional
Level: Detail
Usage: Optional
Max Use: >1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:
Notes:

Ameren - Utility to RES: Required
Ameren - RES to Utility: Required if Dropping by Service Point
ComEd: Not Used

Ameren currently uses an 8-digit Service Point number. All 8 digits, including leading zeros must be provided.

Please see Ameren documentation for which accounts may be dropped at the Service Point level. Mass Market accounts may only be dropped at an account level.
REF~LU~00034180

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification LU Location Number Service Point Identifier	M ID 2/3
Must Use	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier Service Point Identifier	X AN 1/30

Segment: **REF** Reference Identification (Status Reason Code)
Position: 030
Loop: LIN Optional
Level: Detail
Usage: Optional
Max Use: >1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:
Notes:

RES to Utility: Not Used
 Utility to RES: Required
 REF~1P~CHA
 REF~1P~B38~ACCOUNT FINALLED

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification 1P Accessorial Status Code Drop Reason Code	M ID 2/3
Must Use	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier 020 Customer moved or account closed B38 Dropped for Other Reason CHA Customer switched EB3 Customer rescinded enrollment request within rescission period	X AN 1/30
	REF03	352	Description A free-form description to clarify the related data elements and their content Drop Reason Text	X AN 1/80

Segment: **DTM** Date/Time Reference (Requested Off-Cycle Drop Date)
Position: 040
Loop: LIN Optional
Level: Detail
Usage: Optional
Max Use: >1
Purpose: To specify pertinent dates and times
Syntax Notes:

- 1 At least one of DTM02 DTM03 or DTM05 is required.
- 2 If DTM04 is present, then DTM03 is required.
- 3 If either DTM05 or DTM06 is present, then the other is required.

Semantic Notes:

Comments:

Notes:

Ameren: Required for Off-Cycle Drop, otherwise not used.
 ComEd: Not Used

If LIN contains an SW identifier, then DTM~MRR must also be sent. Otherwise, the response will contain REF~1P~W08 and the drop will be scheduled for the next scheduled meter read.

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	DTM01	374	Date/Time Qualifier	M ID 3/3
			Code specifying type of date or time, or both date and time	
			MRR	Meter Reading
				The date the RES would like to have the meter read and the customer dropped from the RES's service. This will not change the meter read cycle.
Must Use	DTM02	373	Date	X DT 8/8
			Date expressed as CCYYMMDD	
			Requested Off-Cycle Drop Date	

Segment: **DTM** Date/Time Reference (Requested On-Cycle Drop Date)
Position: 040
Loop: LIN Optional
Level: Detail
Usage: Optional
Max Use: >1
Purpose: To specify pertinent dates and times
Syntax Notes:

- 1 At least one of DTM02 DTM03 or DTM05 is required.
- 2 If DTM04 is present, then DTM03 is required.
- 3 If either DTM05 or DTM06 is present, then the other is required.

Semantic Notes:

Comments:

Notes:

Required if requesting a drop to occur on-cycle but not necessarily on the next scheduled meter read date. Essentially, it is a "drop no earlier than" date. This date must be within 45 days of the date the drop transaction is processed by the Utility.

If the date provided is beyond the next scheduled meter read date, and within 45 days of the date the utility processes the enrollment, the drop will occur on the following meter read date.

If the date provided is not within 45 days, the utility will reject the transaction.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	DTM01	374	Date/Time Qualifier Code specifying type of date or time, or both date and time 007 Effective	M ID 3/3
Must Use	DTM02	373	Date Date expressed as CCYYMMDD Requested Future On-Cycle Drop Date	X DT 8/8

Segment: **DTM** Date/Time Reference (Service Period End Date)

Position: 040

Loop: LIN Optional

Level: Detail

Usage: Optional

Max Use: >1

Purpose: To specify pertinent dates and times

Syntax Notes: 1 At least one of DTM02 DTM03 or DTM05 is required.

2 If DTM04 is present, then DTM03 is required.

3 If either DTM05 or DTM06 is present, then the other is required.

Semantic Notes:

Comments:

Notes:

RES to Utility - Not Used

Utility to RES - Required

DTM~151~20100530

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
Must Use	DTM01	374	Date/Time Qualifier	M ID 3/3
			Code specifying type of date or time, or both date and time	
			151 Service Period End	
Must Use	DTM02	373	Date	X DT 8/8
			Date expressed as CCYYMMDD	
			Service Period End Date	

Segment: **SE** Transaction Set Trailer
Position: 150
Loop:
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Syntax Notes:

Semantic Notes:

Comments: 1 SE is the last segment of each transaction set.

Notes: Required

SE~13~000000001

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	SE01	96	Number of Included Segments Total number of segments included in a transaction set including ST and SE segments	M N0 1/10
Must Use	SE02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9

Transaction Examples

RES to Utility

(Note this is an example from one RES, there may be multiple variations in practice.)

Before:

ST*814*0001
BGN*13*RESCOMED200807310001*20080731
N1*8S*COMMONWEALTH EDISON*1*006929509**40
N1*SJ*RES COMPANY*1*01111111**41
LIN*1*SH*EL*SH*CE
ASI*F*024
REF*12*1230157111
REF*TN*200807310001
NM1*MQ*2*CUST NAME
N3*I
N4*UNKNOWN*IL*00000
REF*MG*079163111
SE*13*0001

After:

ST*814*0001
BGN*13*RESCOMED200807310001*20080731
N1*8S*COMMONWEALTH EDISON*1*006929509
N1*SJ*RES COMPANY*1*01111111
LIN*200807310001*SH*EL*SH*CE
ASI*F*024
REF*11*00011132
REF*12*1230157111
SE*9*0001

Utility to RES

Before:

ST*814*0003
BGN*13*110000000000000012112967*20080807
N1*8S*COMED*1*006929509**41
N1*SJ*SUPPLIER*1*01111111**40
LIN*1*SH*EL*SH*CE
ASI*F*024
REF*BLT*DUAL
REF*1P*B38
REF*12*0312345624
REF*TN*1
REF*65*2.
DTM*151*20080708
AMT*7N*1
NM1*MQ*2*CUSTOMER NAME
N3*350 MAIN STREET
N4*CARPENTERSVILLE*IL*60110
PER*IC**TE*847555-6331
REF*MG*160124124
SE*19*0003

After:

ST*814*0003
BGN*13*110000000000000012112967*20080807
N1*8S*COMED*1*006929509
N1*SJ*SUPPLIER*1*01111111
N1*8R*CUSTOMER NAME
PER*IC**TE*6305551212
LIN*1*SH*EL*SH*CE
ASI*F*024
REF*1P*B38
REF*11*123456
REF*12*0312345624
DTM*151*20080708
SE*11*0003