

**Segment:** **ST** Transaction Set Header  
**Position:** 010  
**Loop:**  
**Level:** Heading  
**Usage:** Mandatory  
**Max Use:** 1  
**Purpose:** To indicate the start of a transaction set and to assign a control number  
**Syntax Notes:**  
**Semantic Notes:** 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).  
**Comments:**  
**Notes:** Required  
 ST~814~000000001

**Data Element Summary**

	<b>Ref.</b>	<b>Data</b>	<b>Attributes</b>
	<b>Des.</b>	<b>Element Name</b>	
Must Use	ST01	143 Transaction Set Identifier Code	M ID 3/3
		Code uniquely identifying a Transaction Set	
		814 General Request, Response or Confirmation	
Must Use	ST02	329 Transaction Set Control Number	M AN 4/9
		Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	

**Segment:** **BGN** Beginning Segment  
**Position:** 020  
**Loop:**  
**Level:** Heading  
**Usage:** Mandatory  
**Max Use:** 1  
**Purpose:** To indicate the beginning of a transaction set  
**Syntax Notes:** 1 If BGN05 is present, then BGN04 is required.  
**Semantic Notes:** 1 BGN02 is the transaction set reference number.  
 2 BGN03 is the transaction set date.  
 3 BGN04 is the transaction set time.  
 4 BGN05 is the transaction set time qualifier.  
 5 BGN06 is the transaction set reference number of a previously sent transaction affected by the current transaction.

**Comments:**

**Notes:**

Required  
 BGN~11~20091216ABC0000000000000123456~20091216~~~20091215123000001

**Data Element Summary**

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	BGN01	353	<b>Transaction Set Purpose Code</b> Code identifying purpose of transaction set 11 Response	M ID 2/2
Must Use	BGN02	127	<b>Reference Identification</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier A unique transaction identification number assigned by the originator of this transaction. This number must be unique over time. Transaction Reference numbers will only contain uppercase letters (A to Z) and digits (0 to 9). Note that punctuation (spaces, dashes, etc.) must be excluded.	M AN 1/30
Must Use	BGN03	373	<b>Date</b> Date expressed as CCYYMMDD The transaction creation date - the date that the data was processed by the sender's application system.	M DT 8/8
Must Use	BGN06	127	<b>Reference Identification</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier Transaction Reference Number from the BGN02 of the Request Transaction.	O AN 1/30

**Segment:** **N1** Name (Utility)  
**Position:** 040  
**Loop:** N1 Optional  
**Level:** Heading  
**Usage:** Optional  
**Max Use:** 1  
**Purpose:** To identify a party by type of organization, name, and code  
**Syntax Notes:** 1 At least one of N102 or N103 is required.  
 2 If either N103 or N104 is present, then the other is required.  
**Semantic Notes:**  
**Comments:** 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.  
 2 N105 and N106 further define the type of entity in N101.  
**Notes:** Required  
 N1~8S~UTILITY NAME~1~007909411

**Data Element Summary**

	<u>Ref.</u>	<u>Data</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u> <u>Name</u>	<u>M</u> <u>ID</u> <u>2/3</u>
Must Use	N101	98 Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual 8S Consumer Service Provider (CSP) Utility	X AN 1/60
Must Use	N102	93 Name Free-form name Utility Name	X AN 1/60
Must Use	N103	66 Identification Code Qualifier Code designating the system/method of code structure used for Identification Code (67) 1 D-U-N-S Number, Dun & Bradstreet 9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix	X ID 1/2
Must Use	N104	67 Identification Code Code identifying a party or other code Utility D-U-N-S or D-U-N-S+4 Number	X AN 2/80

**Segment:** **N1** Name (Retail Electric Supplier)  
**Position:** 040  
**Loop:** N1 Optional  
**Level:** Heading  
**Usage:** Optional  
**Max Use:** 1  
**Purpose:** To identify a party by type of organization, name, and code  
**Syntax Notes:** 1 At least one of N102 or N103 is required.  
 2 If either N103 or N104 is present, then the other is required.  
**Semantic Notes:**  
**Comments:** 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.  
 2 N105 and N106 further define the type of entity in N101.  
**Notes:** Required  
 N1~SJ~RES COMPANY~1~049612345

**Data Element Summary**

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>	<u>Entity Identifier Code</u>	<u>M ID 2/3</u>
Must Use	N101	98	Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual SJ Service Provider Retail Electric Supplier (RES)	
Must Use	N102	93	Name Free-form name RES Name	X AN 1/60
Must Use	N103	66	Identification Code Qualifier Code designating the system/method of code structure used for Identification Code (67) 1 D-U-N-S Number, Dun & Bradstreet 9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix	X ID 1/2
Must Use	N104	67	Identification Code Code identifying a party or other code RES D-U-N-S or D-U-N-S+4 Number	X AN 2/80

**Segment:** **N1** Name (Customer)  
**Position:** 040  
**Loop:** N1 Optional  
**Level:** Heading  
**Usage:** Optional  
**Max Use:** 1  
**Purpose:** To identify a party by type of organization, name, and code  
**Syntax Notes:** 1 At least one of N102 or N103 is required.  
 2 If either N103 or N104 is present, then the other is required.  
**Semantic Notes:**  
**Comments:** 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.  
 2 N105 and N106 further define the type of entity in N101.  
**Notes:** Required  
 N1~8R~CUSTOMER NAME

**Data Element Summary**

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	N101	98	Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual 8R Consumer Service Provider (CSP) Customer Customer Name	M ID 2/3
Must Use	N102	93	Name Free-form name Customer Name	X AN 1/60

<b>Segment:</b>	<b>LIN</b> Item Identification
<b>Position:</b>	010
<b>Loop:</b>	LIN Optional
<b>Level:</b>	Detail
<b>Usage:</b>	Optional
<b>Max Use:</b>	1
<b>Purpose:</b>	To specify basic item identification data
<b>Syntax Notes:</b>	<ol style="list-style-type: none"> <li>1 If either LIN04 or LIN05 is present, then the other is required.</li> <li>2 If either LIN06 or LIN07 is present, then the other is required.</li> <li>3 If either LIN08 or LIN09 is present, then the other is required.</li> <li>4 If either LIN10 or LIN11 is present, then the other is required.</li> <li>5 If either LIN12 or LIN13 is present, then the other is required.</li> <li>6 If either LIN14 or LIN15 is present, then the other is required.</li> <li>7 If either LIN16 or LIN17 is present, then the other is required.</li> <li>8 If either LIN18 or LIN19 is present, then the other is required.</li> <li>9 If either LIN20 or LIN21 is present, then the other is required.</li> <li>10 If either LIN22 or LIN23 is present, then the other is required.</li> <li>11 If either LIN24 or LIN25 is present, then the other is required.</li> <li>12 If either LIN26 or LIN27 is present, then the other is required.</li> <li>13 If either LIN28 or LIN29 is present, then the other is required.</li> <li>14 If either LIN30 or LIN31 is present, then the other is required.</li> </ol>
<b>Semantic Notes:</b>	1 LIN01 is the line item identification
<b>Comments:</b>	<ol style="list-style-type: none"> <li>1 See the Data Dictionary for a complete list of IDs.</li> <li>2 LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.</li> </ol>
<b>Notes:</b>	<p>Required</p> <p>Ameren: One LIN Loop may be sent for each Service Point on an Account. ComEd: Only One LIN Loop may be sent per 814 transaction LIN~1~SH~EL~SH~CE</p>

#### Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	LIN01	350	<b>Assigned Identification</b> Alphanumeric characters assigned for differentiation within a transaction set The identifier provided in the LIN01 of the Request Transaction.	<b>O AN 1/20</b>
Must Use	LIN02	235	<b>Product/Service ID Qualifier</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234) SH Service Requested	<b>M ID 2/2</b>
Must Use	LIN03	234	<b>Product/Service ID</b> Identifying number for a product or service EL Electric	<b>M AN 1/48</b>
Must Use	LIN04	235	<b>Product/Service ID Qualifier</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234) SH Service Requested	<b>X ID 2/2</b>
Must Use	LIN05	234	<b>Product/Service ID</b> Identifying number for a product or service HI Historical Interval Usage HU Historical Usage	<b>X AN 1/48</b>

**Segment:** **ASI** Action or Status Indicator  
**Position:** 020  
**Loop:** LIN Optional  
**Level:** Detail  
**Usage:** Optional  
**Max Use:** 1  
**Purpose:** To indicate the action to be taken with the information provided or the status of the entity described

**Syntax Notes:**  
**Semantic Notes:**  
**Comments:**  
**Notes:**

Required  
ASI~WQ~029

**Data Element Summary**

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	ASI01	306	<b>Action Code</b> Code indicating type of action U Reject WQ Accept	M ID 1/2
Must Use	ASI02	875	<b>Maintenance Type Code</b> Code identifying the specific type of item maintenance 029 Inquiry	M ID 3/3

**Segment:** **REF** Reference Identification (RES Account Number)  
**Position:** 030  
**Loop:** LIN Optional  
**Level:** Detail  
**Usage:** Optional  
**Max Use:** >1  
**Purpose:** To specify identifying information  
**Syntax Notes:**

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

**Semantic Notes:**

- 1 REF04 contains data relating to the value cited in REF02.

**Comments:**  
**Notes:** Required if provided on the 814 Enrollment or 814 Change transactions.  
REF~11~1234567890

**Data Element Summary**

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification 11 Account Number Retail Electric Supplier (RES) Account Number	M ID 2/3
Must Use	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier RES Account Number	X AN 1/30

**Segment:** **REF** Reference Identification (Utility Account Number)  
**Position:** 030  
**Loop:** LIN Optional  
**Level:** Detail  
**Usage:** Optional  
**Max Use:** >1  
**Purpose:** To specify identifying information  
**Syntax Notes:**

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

**Semantic Notes:**

- 1 REF04 contains data relating to the value cited in REF02.

**Comments:**  
**Notes:**

Required

Both utilities currently have 10 digit account numbers. All 10 digits, including leading zeros must be provided.  
 REF~12~0000445648

**Data Element Summary**

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification 12 Billing Account Utility Account Number	M ID 2/3
Must Use	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier Utility Account Number	X AN 1/30

**Segment:** **REF** Reference Identification (Service Point Identifier)  
**Position:** 030  
**Loop:** LIN Optional  
**Level:** Detail  
**Usage:** Optional  
**Max Use:** >1  
**Purpose:** To specify identifying information  
**Syntax Notes:**

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

**Semantic Notes:**

- 1 REF04 contains data relating to the value cited in REF02.

**Comments:**  
**Notes:**

Ameren - Required <-- QUESTION: If RES submits request without Service Point, will the Service Point(s) be provided on the response?  
 ComEd - Not Used

Ameren currently uses an 8-digit Service Point number. All 8 digits, including leading zeros must be provided.  
 REF~LU~00034180

**Data Element Summary**

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification LU Location Number Service Point Identifier	M ID 2/3
Must Use	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier Service Point Identifier	X AN 1/30

**Segment:** **REF** Reference Identification (Rejection Reason Code)  
**Position:** 030  
**Loop:** LIN Optional  
**Level:** Detail  
**Usage:** Optional  
**Max Use:** >1  
**Purpose:** To specify identifying information  
**Syntax Notes:**

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

**Semantic Notes:**

- 1 REF04 contains data relating to the value cited in REF02.

**Comments:**  
**Notes:**

Accept Response: Not Used  
 Reject Response: Required  
 REF~7G~A76

**Data Element Summary**

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	<b>Reference Identification Qualifier</b> Code qualifying the Reference Identification 7G Data Quality Reject Reason	M ID 2/3
Must Use	REF02	127	<b>Reference Identification</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier A76 Account Not Found	X AN 1/30

**What other Rejection Reasons are Necessary?**

**Segment:** **REF** Reference Identification (URL)  
**Position:** 030  
**Loop:** LIN Optional  
**Level:** Detail  
**Usage:** Optional  
**Max Use:** >1  
**Purpose:** To specify identifying information  
**Syntax Notes:**

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

**Semantic Notes:**

- 1 REF04 contains data relating to the value cited in REF02.

**Comments:**  
**Notes:**

HI Accept Response: Required if available  
 All Other Responses: Not Used  
 REF\*URL\*\*www.comedpowerpath.com/datarequest/DIGEX\_RIF.ASP?R=X12345&P=0123

**Data Element Summary**

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification URL Uniform Resource Locator	M ID 2/3
Must Use	REF03	352	Description A free-form description to clarify the related data elements and their content URL where Historical Interval Usage may be found.	X AN 1/80

**Segment:** **SE** Transaction Set Trailer  
**Position:** 150  
**Loop:**  
**Level:** Detail  
**Usage:** Mandatory  
**Max Use:** 1  
**Purpose:** To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

**Syntax Notes:**

**Semantic Notes:**

**Comments:** 1 SE is the last segment of each transaction set.

**Notes:** Required

SE~13~000000001

#### Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	SE01	96	Number of Included Segments Total number of segments included in a transaction set including ST and SE segments	M N0 1/10
Must Use	SE02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9

Current Example:

ST\*814\*0037  
BGN\*11\*1299923960\*20080905\*\*12012439600001  
N1\*8S\*COMED\*1\*006929509\*\*41  
N1\*SJ\*SUPPLIER\*1\*011111111\*\*40  
LIN\*1\*SH\*EL\*SH\*HI  
ASI\*WQ\*029  
REF\*12\*1310011005  
REF\*URL\*\*www.comedpowerpath.com/datarequest/DIGEX\_RIF.ASP?R=X12345&P=0123  
DTM\*007\*20080905  
NM1\*MQ\*2\*CUSTOMER NAME  
REF\*MG\*078911746  
SE\*12\*0037

New Example:

ST\*814\*0037  
BGN\*11\*1299923960\*20080905\*\*12012439600001  
N1\*8S\*COMED\*1\*006929509  
N1\*SJ\*SUPPLIER\*1\*011111111  
N1\*8R\*CUSTOMER NAME  
LIN\*1\*SH\*EL\*SH\*HI  
ASI\*WQ\*029  
REF\*11\*1234567  
REF\*12\*1310011005  
REF\*URL\*\*www.comedpowerpath.com/datarequest/DIGEX\_RIF.ASP?R=X12345&P=0123  
SE\*11\*0037

HU – Would there be an 814 Accept Response or is the 867 HU sufficient?